



- NOTES:
 1) SHOWN WIRED FOR 480VAC
 2) O INDICATES PLUG IN CONNECTIONS
 3) 15-60A FANS NOT REQUIRED
 4) 15-25A THERMOSTATS NOT AVAILABE, 60A MODELS THERMOSTATS OPTIONAL
 5) BLOWN FUSE INDICATOR NOT AVAILABLE ON 15 & 25A MODELS

THIS DRAWING AND ALL INFORMATION CONTAINED HEREIN, IS THE PROPERTY OF AMETEK HDR POWER SYSTEMS. MAY NOT BE COPIED, REPRODUCED OR DIVULGED TO UNAUTHORIZED PERSONS WITHOUT THE EXPRESS WRITTEN CONSENT OF HDR POWER SYSTEMS.

REVISIONS				REVISIONS				REVISIONS				REVISIONS				REVISIONS								
CHANGE NO.	ECO NO.	DESCRIPTION	DATE	BY	APP	CHANGE NO.	ECO NO.	DESCRIPTION	DATE	BY	APP	CHANGE NO.	ECO NO.	DESCRIPTION	DATE	BY	APP	CHANGE NO.	ECO NO.	DESCRIPTION	DATE	BY	APP	
												1	14-H007	REVISED TITLE AND NOTES	4/28/14	JA	SW							

AMETEK
 HDR POWER SYSTEMS

DRAWN BY/DATE: JF 10/19/07
 SCALE: NTS
 TOLERANCES: (+/-) 0.005
 CHECK'D: GAS
 APP'D BY: GAS
 CUSTOMER: _____

DRAWING NO.: S2710140
 SHEET 1 OF 1
 REVISION 1

TITLE: SCHEMATIC SHZF2 15-225A